

www.synergys-technologies.com

LEAKSHOOTER® LKS1000-V2

Ultrasonic compressed air, gas and vacuum leak detector with camera.

Compressed air is a costly form of energy and 20 to 40% of it is lost through leaks.


Systematically checking for and eliminating leaks can therefore bring considerable energy savings.

Film, view and photograph the precise spot where compressed air, steam, pressurised gas and vacuums are leaking using the LEAKSHOOTER® LKS1000-V2.

The LEAKSHOOTER® LKS1000-V2⊕ is a sophisticated tool. Extremely sensitive, it is capable of finding all leaks, even the smallest, including those no bigger than the size of a syringe needle, at a distance of 20 metres. Leaks can be detected in all types of industrial environment thanks to the possibility of adjusting the gain on the device to filter out all undesirable noise.

The LEAKSHOOTER® LKS1000-V2 is used like a camera. When it comes near a leak, a dynamic white target appears on the large colour screen. The target shrinks as it approaches the source of the leak. A bar graph at the bottom of the screen accompanies and facilitates the search.

When the device is facing the leak, a cross appears around the centre of the target. It is then possible to photograph and save the precise location of the leak.



The photos can be uploaded directly onto a PC via a USB cable (supplied), ready to be attached to inspection reports.

It is still possible, whilst visually searching for a leak, to use the traditional method of leak detection, listening for the hissing sound of the leak using the professional headphones also supplied, which can be plugged directly into the device.

Various accessories are available for the LEAKSHOOTER® LKS1000-V2 enabling it to be used for other applications as well as leak detection.



Detection in hard to reach areas with sensor: LKSFLEX – Flexible probe 400mm long LKSFLEX1500 – Flexible probe 1500 mm long



For Steam trap control:

LKSPROBE

Mechanical US Sensor



Tightness and sealing control: LKSDOME Ultrasonic emitter with 13 emitters



Listening : LKSHEAD – Bluetooth Headphones



Listening: LKSSPEAKER Bluetooth Speaker



Kons - © Fort Awasoma | Graphism - © Natacha Nisssbaum | Pl EASE DO NOT LITTER

SPECIFICATIONS LKS1000-V2

| ς | ensitivity | |
|---|--------------------|---|
| 3 | Charlettey | Detects a leak of 0,1 mm at 3 bars at 20 m |
| C | Camera | Colour 640 x 480 pixels + LED lighting |
| D | Display | LCD colour 5.7" 640 x 480 pixels |
| Р | rictures | BMP, number, name, date and time |
| | | White circle for leak detection Colored circle with cross for the leak severity |
| N | Measurements | dB RMS and MAX RMS |
| N | Memory | Up to 1000 pictures, can be uploaded to PC |
| C | Communication | USB cable supplied |
| U | | Open type - Bandwidth \pm 2 kHz to - 6 dB - Central frequency 40 kHz \pm 1 kHz - Adjustable frequency mixer from 30 to 50 kHz - Adjustable gain from 40 to 120 dB |
| Н | leadphones | Adjustable volume |
| Р | ower supply | Nickel-metal hybride (NiMH) |
| А | utonomy | 6 hours |
| | emperature ange | - 10°C to + 50°C |
| D | Dimensions | H: 310 mm - W: 165 mm - D: 65 mm |
| V | | 700 gr for the LKS1000 3,8 kg including ABS case |
| C | E Standards | CEM 2004/108/CE : EN61000-6-4 & EN61000-6-2 |
| A | ccessories | Ultrasonic emitter Reference: LKSDOME Flexible 400 mm US Sensor Reference: LKSFLEX Flexible 1500 mm US Sensor Reference: LKSFLEX1500 Mechanical US sensor (steam trap - bearing) Reference: LKSPROBE Bluetooth headphones Reference: LKSHEAD Bluetooth Speaker Reference: LKSSPEAKER |



LEAKSHOOTER® a SYNERGYS TECHNOLOGIES innovation

Distributed by: